

FEB 19 2004

TRANSMITTAL LETTER
(General - Patent Pending)

Docket No.
C-2451

In Re Application Of: Paul R. Margiott; Christopher W. Callahan; Michael L. Perry; and Glenn W. Scheffler

Serial No.
09/992,591

Filing Date
11/06/2001

Examiner

Group Art Unit
1745

Title: Shut-down Procedure for Fuel Cell Fuel Processing System

TO THE COMMISSIONER FOR PATENTS:

Transmitted herewith is:

A Response to First Office Action

in the above identified application.

No additional fee is required.
 A check in the amount of _____ is attached.
 The Director is hereby authorized to charge and credit Deposit Account No. 50-1307
as described below.
 Charge the amount of _____
 Credit any overpayment.
 Charge any additional fee required.

Signature

Stephen E. Revis


Dated: February 17, 2004

I certify that this document and fee is being deposited on
Feb. 17, 2004 with the U.S. Postal Service as first
class mail under 37 C.F.R. 1.8 and is addressed to the
Commissioner for Patents, P.O. Box 1450, Alexandria, VA
22313-1450.

Signature of Person Mailing Correspondence

CC:

Stephen E. Revis
Typed or Printed Name of Person Mailing Correspondence



IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re application of : Margiott et al

Serial No.: 09/992,591

Filed: 11/06/2001

Docket No.: C-2451

Examiner: Alejandro, Raymond

Group Art Unit: 1745

Title: Shut-down Procedure for Fuel Cell Fuel Processing System

Mail Stop Non-Fee Amendment
Commissioner for Patents
P.O. Box 1450
Alexandria, VA 22313-1450

Sir:

RESPONSE TO FIRST OFFICE ACTION

In the Office Action dated January 8, 2004, all the claims (1-17) of the subject application are rejected under 35 U.S.C. 103(a) as being unpatentable over Takechi et al in view of Cameron. For the following reasons, Applicants disagree with the basis for the Examiner's rejection and believe all the claims as originally presented are patentable and should be allowed.

The only independent claim in the application is amended claim 1. The invention is a process for shutting down a fuel cell and its associated fuel processing system, wherein the fuel processing system includes "...a fuel reformer in series flow relationship with a catalytic shift converter..." (claim 1, lines 6-8). During normal fuel cell operation "...organic fuel...is directed, in series, through the fuel reformer, the shift converter, and fuel cell anode flow field..." (claim 1, lines 8-12). As set forth in claim 1 at lines 15-19, the steps of the shut-down procedure comprise:

- a. disconnecting the load from the cell and halting the flow of organic fuel from the source to the fuel processing system; and then
- b. purging the reformer of residual hydrogen by flowing air through the reformer.

Step b. of claim 1 is a novel and unobvious step of the shut down procedure and is not shown or made obvious from any of the art of record.

Claim 3 is dependent upon claim 1 and further requires that the fuel cell anode flow field, as well as the reformer “are purged of residual hydrogen by passing air, in series, through the reformer and thereafter through the fuel cell anode flow field.” (emphasis added)

The fuel cell system described in Takechi et al shows a catalytic fuel reformer in series with a fuel cell, wherein, during normal fuel cell operation, the reformed fuel is passed from the reformer into and through the anode side of the fuel cell. Takechi et al, at the bottom of column 3 and the top of column 4, discusses four conditions that must be met in order for there to be a safe shut-down of the system. None of these conditions, however, requires or suggests purging the fuel reformer of residual hydrogen by passing air therethrough, as is required by all of Applicants' claims. More specifically, Takechi et al's condition #4 requires either reducing the temperature of the reformer catalyst bed to deactivate it, or purging the bed with an inert gas. Takechi et al describes using air (introduced by a blower 11) to cool the catalyst bed; but that air simply passes around (i.e. in heat exchange relationship with) the catalyst bed, and does not purge residual hydrogen from the reformer, as required by Applicants' claims.

Takechi et al does describe the use of an air purge or inert gas purge for the cathode side of the cell (column 4, lines 29-34), but not for the anode side as required by Applicants' claim 3, which also requires that the air used to purge the reformer be thereafter passed through the anode side of the cell.

Additionally, the Examiner, on the top of page 5 of the office action, emphasizes that the Takechi et al burners 7m, 7h “are in fluid communication with the fuel cell 2”, and that the valve 24 is connected to the fuel cell “allowing the selection of either low temperature atmospheric air or high temperature air from the fuel processor 1.” It is not understood how this relates to Applicants’ invention. What is actually shown and described in Takechi et al is the use of the residual hydrogen in the fuel cell anode exhaust stream as fuel for the burners 7, and the use of air from the valve 24 as a purge gas for the cathode side of the cell. Note that nothing except hydrogen from the storage tank 16 passes through the anode side of the fuel cell during either fuel cell operation or shut-down.

From the foregoing, it is clear that Takechi et al does not suggest an air purge of the residual hydrogen from the reformer or an air purge of the anode flow field. The Examiner appears to recognize this by stating on page 5 of the office action that “...Takechi et al do not expressly disclose the specific purging steps.”

Cameron is cited by the Examiner for its teaching of the purging of a fuel cell with either an inert gas or with the products of combustion from a combustor. However, Cameron does not suggest, as part of the shut-down procedure, that residual hydrogen be purged from a reformer using air. Cameron does not even use a reformer to provide fuel for the fuel cell during normal cell operation. The combustor of Cameron, even if it were a reformer, is only used (a) to provide heat for the fuel cell (col. 3, lines 43-47) (or for its circulating electrolyte) or (b) to generate inert combustion products (not air) for purging the fuel cell (col. 3, lines 34-36). The combustor itself is not purged upon shut-down of the cell.

To summarize, the arguments set forth on page 6 of the office action as to how the combination of Takechi et al and Cameron make Applicant’s invention obvious are not correct for two basic reasons. First, as set forth above, neither of the cited patents describe or suggest a shut-down procedure that includes an air purge of the residual

hydrogen within a fuel reformer or the air purge of the anode side of the fuel cell. And, second, the steps that the Examiner asserts are made obvious by the combination of Takechi et al and Cameron are not the steps of Applicants' invention. Therefore, Applicants request reexamination of all the claims and allowances thereof.

Respectfully submitted,



Stephen E. Revis
Reg. No. 26,609

Stephen E. Revis
1 Abbottsford
Avon, CT 06001-3953
Tel.: (860) 674-1835

Date: February 17, 2004